



ITEM	SELECTABLE CONTENTS
	STN YELLOW MODE
	STN GRAY MODE
DISPLAY MODE	STN BLUE MODE
	FSTN
POLARIZER TYPE	REFLECTIVE
	TRANSPARENT
	TRANSMISSIVE POSITIVE
	TRANSMISSIVE NEGATIVE
VIEWING DIRECTION	6 O'CLOCK
	12 O'CLOCK
LED BACKLIGHT	WHITE
	Y-G
	RED
	GREEN
	BLUE
	AMBER
	TRI-COLOR
TEMPERATURE RANGE	STANDARD TEMPERATURE
	WIDE TEMPERATURE
OPERATING VOLTAGE	5.0V
LED DRIVING VOLTAGE	6.5V
LCD DRIVE METHOD	1/32 DUTY 1/5 BIAS
LCD DRIVE IC	PT6520 OR EQUIV

**NOTE:**

1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.

THE PART NUMBER IN MASS PRODUCTION	
1.STN(GRAY)/POSITIVE/TRANSPARENT;BL:Y-G LED BACKLIGHT;6 O'CLOCK;	
2.FSTN/POSITIVE/TRANSPARENT;BL:WHITE LED BACKLIGHT;12 O'CLOCK;	
UNIT	TOLERANCE
MM	X.X = ±0.2
3RD ANGLE	X.XX = ±0.10
ANG =	-
SCALE:	1:1
DRAWN:	TITLE: LCM
CHECKED:	MODEL NO: AGM1232G SERIES
APPROVED:	PART NO:
	REV A
	SH NO 1/1