



ITEM	SELECTABLE CONTENTS
DISPLAY MODE	STN YELLOW MODE STN GRAY MODE STN BLUE MODE FSTN
POLARIZER TYPE	REFLECTIVE TRANSPARENT TRANSMISSIVE POSITIVE TRANSMISSIVE NEGATIVE
VIEWING DIRECTION	6 O'CLOCK 12 O'CLOCK
LED BACKLIGHT	WHITE Y-G RED GREEN BLUE AMBER
TEMPERATURE RANGE	TR-COLOR STANDARD TEMPERATURE WIDE TEMPERATURE
OPERATING VOLTAGE	5.0V
LED DRIVING VOLTAGE	6.5V
LED DRIVE METHOD	1/32 DUTY 1/5 BIAS
LED DRIVE IC	ST7920-OB-B OR EQUIV

**NOTE:**  
1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.

THE PART NUMBER IN MASS PRODUCTION	
1.STN(BLUE)/NEGATIVE/TRANSMISSIVE ;BL:WHITE LED BACKLIGHT;6 O'CLOCK;	
UNIT: MM	
3RD ANGLE	
SCALE: 1:1	
DRAWN: _____	
CHECKED: _____	
APPROVED: _____	
TITLE: LCM	
MODEL NO: AGM1232GA SERIES	
PART NO: _____	
TOLERANCE: X.X = ±0.2	
X.XX = ±0.10	
ANG = -	
<b>AZ DISPLAYS</b>	
REV	A
SH NO	1/1