



ITEM	SELECTABLE CONTENTS
	STN YELLOW MODE
	STN GRAY MODE
DISPLAY MODE	STN BLUE MODE
	FSTN
	REFLECTIVE
	TRANSPARENT
POLARIZER TYPE	TRANSMISSIVE, POSITIVE
	TRANSMISSIVE, NEGATIVE
VIEWING DIRECTION	6 O'CLOCK
	12 O'CLOCK
	WHITE
	Y-G
	RED
	GREEN
	BLUE
	AMBER
LED BACKLIGHT	TRICOLOR
	STANDARD TEMPERATURE
TEMPERATURE RANGE	WIDE TEMPERATURE
OPERATING VOLTAGE	5.0V
LCD DRIVING VOLTAGE	9.5V
LCD DRIVE METHOD	1/64 DUTY 1/9 BIAS
LCD DRIVE IC	SBN0064G-D OR EQUIV

NOTE:
 1. The power supply for backlight is depended on the backlight color and the value of current-limiting resistance.

1	2	3	4	5	6	7	8
<p>THE PART NUMBER IN MASS PRODUCTION</p> <p>1.STN(Y-G)/POSITIVE/TRANSPARENT;:B.L:Y-G LED BACKLIGHT;6 O'CLOCK;</p>							
<p>UNIT</p> <p>MM</p> <p>3RD ANGLE</p> <p>SCALE: 1:1</p>				<p>TOLERANCE</p> <p>X.XX = ±0.2</p> <p>X.XX = ±0.10</p> <p>ANG = -</p>			
<p>DRAWN:</p> <p>CHECKED:</p> <p>APPROVED:</p>				<p>TITLE: LCM</p> <p>MODEL NO: AGM12640 SERIES</p> <p>PART NO:</p>			
				<p>REV A</p> <p>SH NO 1/1</p>			

AZ DISPLAYS